



Keeping firefighters safe, effective & productive

Firecom 50 Series Wired

UH-52 UNDER-HELMET HEADSET

CONFIGURATION		
	Transmit	Receive
Intercom	PTT	Yes
Radio		Yes

The Firecom UH-52 wired headset delivers all the benefits of hands-free, full-duplex communication with your crew. Operating with a stand-alone intercom system or integrated with a mobile radio, the flexible design brings all crew members into constant communication. Behind-the-head band configuration with adjustable over-head strap easily accommodates use with helmets. Water-resistant and comfortable ear seals, extended operating temperature, and robust design make this headset ready for action in virtually any fireground environment.

Extended-range operating temperature

Rated from -40°F to +158°F, this headset works wherever you do

PTT intercom

Black PTT button to talk over intercom: listen-only intercom and radio when button not engaged



Three-way adjustable boom

Precise microphone placement, comfort, and performance



Glove-rugged plug

Ergonomic connector is easy to grasp with a gloved hand and will swivel to distribute strain at the jack connection

Memory foam ComLeather ear seals

Fit comfortably for hours while delivering 24db noise reduction





Keeping firefighters safe, effective & productive

FEATURES

State-of-the-art ear and hearing protection	Enhanced microphone
ComLeather over memory foam ear seals for hours of comfortable use	Flexible mic. boom with slide adjustment for accurate/secure positioning
Enhanced durability and comfort, designed to fit any head size	Microphone boom rotates for left or right dress
24dB noise reduction rating (NRR)	Noise-cancelling electret microphone ensures optimal clarity
IP65 rating for dust/water protection when worn	Programmable microphone gain
Total configurability	Microphone protected by a layer of waterproof material for outdoor use
Push-to-talk intercom plus listen-only radio	Microphone muff improves clarity by eliminating wind noise
Communicates over intercom with push-to-talk transmit button	Simple maintenance
PTT button requires solid push, eliminating accidental transmissions	Black domes for easy cleaning
Custom programmable to user specifications	Black powder-coated headband for durability
	Glove-rugged plug for longer life

SPECIFICATIONS

Physical	Environmental
Weight: 19 oz.	IP-65 rated, when worn
Color: Black	Operating temperature -40°F (-40°C) to +158°F (+70°C)
Noise Reduction Rating: 24dB NRR	Storage temperature -40°F (-40°C) to +185°F (+85°C)
SAE	Charging Temperature 32°F (0°C) to +104°F (+40°C)
Salt Spray per J1455, Sec. 4.3	MIL
ISO	Humidity per MIL-STD 810F and 810G
Conducted Transients per 7637-2	Temperature Shock per MIL-STD 810F and 810G
	Chemical Exposure per MIL-STD 810F and 810G

FIRECOM - A division of Sonetics Corporation

7340 SW Durham Rd. | Portland, OR 97224 USA | 800-527-0555 • 503-684-6647 | fax: 503-620-2943 | www.firecom.com